	NOTES: 1. ALL PARTS TO BE BULK PACKED. 2. SOLDER CONTACTS ARE PRESSED INTO CONNECTOR. SIZE 12 CONTACTS AND SIZE 26 CONTACTS (POSITIONS 3, 7, 8) FACE TOP KEY (UP). SIZE 26 CONTACTS (POSITIONS 4-6) FACE DOWN. 3. ALL DIMENSIONS ARE FOR REFERENCE ONLY EXCEPT WHERE NOTED WITH TOLERANCE.	ASSY P/N W5B82-8PG-535	CABLE O.D350400 IN. [8.9-10.2mm]	
CUSTOMER PRINT	TACE VIEW 1.000 0.082 ±0.015 #26 CONTACT SOLDER CUP STYLE MAT'L: COPPER ALLOY GROMMET MAT'L: RUBBER, MAT'L: RUBBER, MAT'L: P MAT'L: UV PBT, BLACK MAT'L: UV PBT, BLACK	0.830 BT, BLACK BAC		KEYWAY
PART W5B82-8PG-5XX	O.75 O.75 THIS DOCUMENT INFORMATION CORPORATION DISCLOSI DOCUMENT IN PROHIBITED WRITING BY COMPANY OF THE PROHIBITED WRI	R APPROVAL CONTAINS CONFIDENTIAL PROPRIETARY TO CONXALL N. ANY REPRODUCTION, IRE, OR USE OF THIS FORMATION IS EXPRESSLY UNLESS AUTHORIZED IN CONXALL CORPORATION. BY: ROHS COMPLIANT	A AB 05-10-19 RELEASE PER DO REV. INIT. DATE DESCRIPTION ALL INFORMATION LUSTRATED IS THE PROPERTY OF "CONVALL OUPLICATION OF DISTRIBUTION OF THIS DOCUMENT IS PROHIBITED ALL UNITS ARE IN FEET, INCHES, FRACTION OF INCHES AND DECIMALS. ALL UNITS ARE IN FEET, INCHES, FRACTION OF INCHES AND DECIMALS. APPROVED BY: SCALE SIZE SHEET NTS B 1 OF FILE: DIRECTOR SAME AS P/N SLV	14 601 E. WILDWOOD VILLA PARK, IL 60181 TITLE CABLE TO CABLE CONNECTOR KIT (2)#12 + (6)#26 PIN CONTACTS, SOLDER CUP MULTI-CON-X, WEATHER RESISTANT CUSTOMER: STANDARD PRODUCT